

Print Page

## Ballistic Charts

Close Window

[Velocity](#)[Energy](#)[Wind Drift](#)[Average Range](#)[Long Range](#)

Jump to: [Load Details](#) | [Velocity](#) | [Energy](#) | [Wind Drift](#) | [Average-Range](#) | [Long-Range](#) | [Bullet Images](#)

## Compare Ballistics

Load Number      Brand:  
 AE223              AMERICAN EAGLE®  
 AE223N            AMERICAN EAGLE®

## Load Details

Federal Load No.	Factory Primer No.	Caliber	Bullet Weight Grains / Grams	Bullet style	T.B*
AE223	205	223 Rem. (5.56x45mm)	55 / 3.56	Full Metal Jacket Boat-Tail	24
AE223N	205	223 Rem. (5.56x45mm)	62 / 4.02	Full Metal Jacket Boat-Tail	24

## Velocity in Feet Per Second

	Muzzle	100	200	300	400	500
AE223	3240	2874	2536	2222	1931	1667
AE223N	3020	2713	2426	2156	1904	1674

## Energy in Foot Pounds

	Muzzle	100	200	300	400	500
AE223	1282	1008	785	603	455	339
AE223N	1255	1013	810	640	499	386

## Wind Drift in Inches 10 MPH Crosswind

	100	200	300	400	500
AE223	1.0	4.3	10.2	19.4	32.7
AE223N	1.0	4.0	9.7	18.1	30.4

## Average Range

	50	100	200	300
AE223	-0.3	⊕	-2.7	-10.9
AE223N	-0.2	⊕	-3.2	-12.4

## Long Range

	50	100	200	300	400	500
AE223	0.4	1.4	⊕	-6.8	-20.6	-44.2
AE223N	0.6	1.6	⊕	-7.6	-22.6	-47.6



Look for the Low Recoil logo on select products for a softer shooting load.  
 T.B\* = Test Barrel Length in Inches.

Close Window