

[Print Page](#)**Ballistic Charts**[Close Window](#)

Jump to: [Load Details](#) | [Velocity](#) | [Energy](#) | [Wind Drift](#) | [Average-Range](#) | [Long-Range](#) | [Bullet Images](#)

Compare Ballistics

Load Number	Brand:
T223E	PREMIUM TACTICAL TRU
T223F	PREMIUM TACTICAL TRU
T223L	PREMIUM TACTICAL TRU
T223M	PREMIUM TACTICAL TRU

Load Details

Federal Load No.	Factory Primer No.	Caliber	Bullet Weight Grains / Grams	Bullet style	T.B*
T223E	no	223 Rem. (5.56x45mm)	55 / 3.56	Sierra® BTHP	24
T223F	no	223 Rem. (5.56x45mm)	55 / 3.56	Nosler® Ballistic Tip®	24
T223L	no	223 Rem. (5.56x45mm)	64 / 4.15	Hi-Shok SP	24
T223M	no	223 Rem. (5.56x45mm)	69 / 4.47	Sierra® MatchKing BTHP	24

Velocity in Feet Per Second

	Muzzle	100	200	300	400	500
T223E	3220	2829	2470	2138	1833	1561
T223F	3220	2853	2514	2199	1908	1644
T223L	3050	2682	2342	2027	1740	1485
T223M	2950	2642	2353	2084	1832	1604

Energy in Foot Pounds

	Muzzle	100	200	300	400	500
T223E	1266	977	745	558	410	298
T223F	1266	994	772	591	444	330
T223L	1322	1022	779	584	430	313
T223M	1333	1069	848	665	514	394

Wind Drift in Inches 10 MPH Crosswind

	100	200	300	400	500
T223E	1.1	4.7	11.3	21.5	36.4
T223F	1.0	4.3	10.4	19.7	33.3
T223L	1.2	4.9	11.8	22.6	38.2
T223M	1.0	4.3	10.3	19.3	32.4


Average Range

	50	100	200	300
T223E	-0.3	⊕	-2.9	-11.5
T223F	-0.3	⊕	-2.8	-11.1
T223L	-0.2	⊕	-3.3	-13.1
T223M	-0.2	⊕	-3.5	-13.3

Long Range

	50	100	200	300	400	500
T223E	0.4	1.4	⊕	-7.2	-22.0	-47.6
T223F	0.4	1.4	⊕	-6.9	-21.0	-45.2

T223L	0.6	1.7	⊕	-8.1	-24.7	-53.2
T223M	0.7	1.7	⊕	-8.1	-24.1	-51.0

 Look for the Low Recoil logo on select products for a softer shooting load.
T.B* = Test Barrel Length in Inches.

Close Window